

Safety Data Sheet



1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: NITRIC ACID 30%

Recommended Use of the Chemical and Restrictions on Use Cleaning in process in the dairy industry.

Supplier: Ixom Operations Pty Ltd
ABN: 51 600 546 512
Street Address: Level 8, 1 Nicholson Street
East Melbourne Victoria 3002
Australia

Telephone Number: +61 3 9906 3000
Emergency Telephone: 1 800 033 111 (ALL HOURS)

Please ensure you refer to the limitations of this Safety Data Sheet as set out in the "Other Information" section at the end of this Data Sheet.

2. HAZARDS IDENTIFICATION

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail; DANGEROUS GOODS.

This material is hazardous according to Safe Work Australia; HAZARDOUS CHEMICAL.

Classification of the chemical:

Corrosive to Metals - Category 1
Skin Corrosion - Sub-category 1A
Eye Damage - Category 1

SIGNAL WORD: DANGER



Hazard Statement(s):

H290 May be corrosive to metals.
H314 Causes severe skin burns and eye damage.

Precautionary Statement(s):

Prevention:

P234 Keep only in original container.
P260 Do not breathe mist, vapours, spray.
P264 Wash hands thoroughly after handling.
P280 Wear protective gloves / protective clothing / eye protection / face protection.

Safety Data Sheet



Response:

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P363 Wash contaminated clothing before re-use.

P321 Specific treatment (see First Aid Measures on Safety Data Sheet).

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor/physician.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P390 Absorb spillage to prevent material damage.

Storage:

P405 Store locked up.

P406 Store in corrosive resistant container with a resistant inner liner.

Disposal:

P501 Dispose of contents and container in accordance with local, regional, national, international regulations.

Poisons Schedule (SUSMP): S6 Poison.

3. COMPOSITION AND INFORMATION ON INGREDIENTS

Components	CAS Number	Proportion	Hazard Codes
Water	7732-18-5	70%	-
Nitric acid	7697-37-2	30%	H272 H290 H314

4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor at once. Urgent hospital treatment is likely to be needed.

Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If patient finds breathing difficult and develops a bluish discoloration of the skin (which suggests a lack of oxygen in the blood - cyanosis), ensure airways are clear of any obstruction and have a qualified person give oxygen through a face mask. Apply artificial respiration if patient is not breathing. Seek immediate medical advice.

Skin Contact:

If spilt on large areas of skin or hair, immediately drench with running water and remove clothing. Continue to wash skin and hair with plenty of water (and soap if material is insoluble) until advised to stop by the Poisons Information Centre or a doctor.

Eye Contact:

Immediately wash in and around the eye area with large amounts of water for at least 15 minutes. Eyelids to be held apart. Remove clothing if contaminated and wash skin. Urgently seek medical assistance. Transport promptly to hospital or medical centre.

Ingestion:

Immediately rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water. Seek immediate medical assistance.

Safety Data Sheet



Indication of immediate medical attention and special treatment needed:

Treat symptomatically. Can cause corneal burns. Material is strongly acidic and corrosive. Effects from exposure to decomposition products including nitrogen dioxide (possible decomposition component) can include chest discomfort, shortness of breath and possible pulmonary oedema, the onset of which may be delayed. The exposed person should be kept under medical surveillance for 24 hours for delayed onset of pulmonary oedema.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media:

Not combustible, however, if material is involved in a fire use: Fine water spray, normal foam, dry agent (carbon dioxide, dry chemical powder).

Hazchem or Emergency Action Code: 2R

Specific hazards arising from the chemical:

Non-combustible material. Corrosive substance.

Special protective equipment and precautions for fire-fighters:

Decomposes on heating emitting toxic fumes, including those of oxides of nitrogen. Brown fumes indicate the presence of toxic oxides of nitrogen. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to products of decomposition. If safe to do so, remove containers from path of fire. Keep containers cool with water spray.

6. ACCIDENTAL RELEASE MEASURES

Emergency procedures/Environmental precautions:

Clear area of all unprotected personnel. If contamination of sewers or waterways has occurred advise local emergency services.

Personal precautions/Protective equipment/Methods and materials for containment and cleaning up:

Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact and breathing in vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal. Neutralise residues with lime or soda ash. Wash area down with excess water.

7. HANDLING AND STORAGE

This material is a Scheduled Poison S6 and must be stored, maintained and used in accordance with the relevant regulations.

Precautions for safe handling:

Avoid skin and eye contact and breathing in vapour, mists and aerosols. Keep out of reach of children. Always add the acid to water, never the reverse.

Conditions for safe storage, including any incompatibilities:

Store in a cool, dry, well ventilated place and out of direct sunlight. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Keep containers closed when not in use - check regularly for leaks.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters: No value assigned for this specific material by Safe Work Australia. However, Workplace Exposure Standard(s) for constituent(s):

Safety Data Sheet



Nitric acid: 8hr TWA = 5.2 mg/m³ (2 ppm), 15 min STEL = 10 mg/m³ (4 ppm)

As published by Safe Work Australia Workplace Exposure Standards for Airborne Contaminants.

TWA - The time-weighted average airborne concentration of a particular substance when calculated over an eight-hour working day, for a five-day working week.

STEL (Short Term Exposure Limit) - the airborne concentration of a particular substance calculated as a time-weighted average over 15 minutes, which should not be exceeded at any time during a normal eight hour work day. According to current knowledge this concentration should neither impair the health of, nor cause undue discomfort to, nearly all workers.

These Workplace Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These workplace exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

Appropriate engineering controls:

Ensure ventilation is adequate and that air concentrations of components are controlled below quoted Workplace Exposure Standards. Keep containers closed when not in use.

If in the handling and application of this material, safe exposure levels could be exceeded, the use of engineering controls such as local exhaust ventilation must be considered and the results documented. If achieving safe exposure levels does not require engineering controls, then a detailed and documented risk assessment using the relevant Personal Protective Equipment (PPE) (refer to PPE section below) as a basis must be carried out to determine the minimum PPE requirements.

Individual protection measures, such as Personal Protective Equipment (PPE):

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

OVERALLS, CHEMICAL GOGGLES, FACE SHIELD, GLOVES (Long), APRON, RUBBER BOOTS.



Wear overalls, chemical goggles, face shield, elbow-length impervious gloves, splash apron or equivalent chemical impervious outer garment, and rubber boots. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

If determined by a risk assessment an inhalation risk exists, wear a suitable mist respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Clear Liquid
Colour:	Colourless
Odour:	Sharp , Irritating
Solubility:	Miscible with water.
Specific Gravity:	ca. 1.2

Product Name: NITRIC ACID 30%
Substance No: 000000017886

Issued: 08/07/2019
Version: 4

Safety Data Sheet



Relative Vapour Density (air=1):	Not available
Vapour Pressure (20 °C):	Not available
Flash Point (°C):	Not applicable
Flammability Limits (%):	Not applicable
Autoignition Temperature (°C):	Not applicable
Boiling Point/Range (°C):	Not available
pH:	Not available

10. STABILITY AND REACTIVITY

Reactivity:	Reacts with strong alkalis. Corrodes metals.
Chemical stability:	Stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.
Possibility of hazardous reactions:	Reacts with metals liberating flammable hydrogen gas. May cause fire in contact with organic materials such as wood, cotton or straw, evolving toxic nitrogen oxides gases (brown fumes).
Conditions to avoid:	Avoid exposure to light. Avoid contact with foodstuffs.
Incompatible materials:	Incompatible with strong alkalis, organic chemicals, reducing agents, carbides, chlorates, metals .
Hazardous decomposition products:	Oxides of nitrogen.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Ingestion:	Swallowing can result in nausea, vomiting, diarrhoea, abdominal pain and chemical burns to the gastrointestinal tract.
Eye contact:	A severe eye irritant. Corrosive to eyes; contact can cause corneal burns. Contamination of eyes can result in permanent injury.
Skin contact:	Contact with skin will result in severe irritation. Corrosive to skin - may cause skin burns.
Inhalation:	Breathing in mists or aerosols may produce respiratory irritation. Nitric acid may decompose to a toxic brown gas of nitrogen dioxide. Inhalation of the gas may result in chest discomfort, shortness of breath and possible pulmonary oedema, the onset of which may be delayed.
Acute toxicity:	No LD50 data available for the product.
Respiratory or skin sensitisation:	No information available.
Chronic effects:	Chronic overexposure to vapour, fumes or aerosols may produce adverse effects on the lungs and erosion of the teeth.
Aspiration hazard:	No information available.

12. ECOLOGICAL INFORMATION

Ecotoxicity	Avoid contaminating waterways.
Persistence/degradability:	No information available.
Bioaccumulative potential:	No information available.
Mobility in soil:	No information available.

13. DISPOSAL CONSIDERATIONS

Disposal methods:

Refer to Waste Management Authority. Dispose of contents and container in accordance with local, regional, national, international regulations.

14. TRANSPORT INFORMATION

Road and Rail Transport

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail; DANGEROUS GOODS.



UN No:	2031
Transport Hazard Class:	8 Corrosive
Packing Group:	II
Proper Shipping Name or Technical Name:	NITRIC ACID
Hazchem or Emergency Action Code:	2R

Marine Transport

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; DANGEROUS GOODS.

UN No:	2031
Transport Hazard Class:	8 Corrosive
Packing Group:	II
Proper Shipping Name or Technical Name:	NITRIC ACID

IMDG EMS Fire:	F-A
IMDG EMS Spill:	S-B

Air Transport

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; DANGEROUS GOODS. TRANSPORT PROHIBITED under the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air in Passenger and Cargo Aircraft; may be transported by Cargo Aircraft Only.

UN No:	2031
---------------	------

Safety Data Sheet



Transport Hazard Class: 8 Corrosive
Packing Group: II
Proper Shipping Name or Technical Name: NITRIC ACID

15. REGULATORY INFORMATION

Classification:

This material is hazardous according to Safe Work Australia; HAZARDOUS CHEMICAL.

Classification of the chemical:

Corrosive to Metals - Category 1
Skin Corrosion - Sub-category 1A
Eye Damage - Category 1

Hazard Statement(s):

H290 May be corrosive to metals.
H314 Causes severe skin burns and eye damage.

Poisons Schedule (SUSMP): S6 Poison.

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

This safety data sheet has been prepared by Ixom Operations Pty Ltd (Toxicology & SDS Services).

Reason(s) for Issue:

5 Yearly Revised Primary SDS
Change in Handling & Storage Requirements

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Ixom Operations Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Ixom representative or Ixom Operations Pty Ltd at the contact details on page 1.

Ixom Operations Pty Ltd's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.